



DETAILED DESCRIPTION
 SENSTEC Anti-Slip shower trays have a unique integrated profile that has been designed to not only increase grip levels, but is also comfortable to stand on and is easily cleaned. EN 14527 Class 1. The base of the Tray must be adequately supported.

ANTI-SLIP PROPERTIES
 UKAS accredited laboratory results. Pendulum Test, BS 7976_2:2002, With the NON REQUIRED addition of contaminant to reflect a showering environment, PTV value of 48. Ramp Test DIN 51097, Ramp angle of 30 degrees, best category classification of C. SENSTEC Anti-Slip properties fall into best possible classifications when tested to BS7976_2:2002 and DIN 51097. User Experience testing carried out by University of Ulster showed 94% very positive.

MATERIAL
 Gelcoat surface, stone resin fill.

DEPTH
 36 mm.

COLOUR
 Available in all colours.

WASTE
 SENSTEC shower trays have been designed exclusively for use with McAlpine ST90CPB-S-HP2 or ST90CPB-S-70, with flow rates of 42 and 34 litres per minute respectively when tested in accordance with EN274-2:2002. <http://mcalpineplumbing.com>

2 Anti-Slip_ShowerTray_Rectangular Detailed Description

| (a) mm | (b) mm | (c) mm | (d) mm | (e) mm | (f) mm |
|--------|--------|--------|--------|--------|--------|
| 1800 | 1000 | 990 | 810 | 180 | 820 |
| 1800 | 900 | 990 | 810 | 180 | 720 |
| 1800 | 800 | 990 | 810 | 180 | 620 |
| 1700 | 1000 | 940 | 760 | 180 | 820 |
| 1700 | 900 | 940 | 760 | 180 | 720 |
| 1700 | 800 | 940 | 760 | 180 | 620 |
| 1700 | 750 | 940 | 760 | 180 | 570 |
| 1700 | 700 | 940 | 760 | 180 | 520 |
| 1600 | 1000 | 890 | 710 | 180 | 820 |
| 1600 | 900 | 890 | 710 | 180 | 720 |
| 1600 | 800 | 890 | 710 | 180 | 620 |
| 1500 | 1000 | 840 | 660 | 180 | 820 |
| 1500 | 900 | 840 | 660 | 180 | 720 |
| 1500 | 800 | 840 | 660 | 180 | 620 |
| 1400 | 1000 | 790 | 610 | 180 | 820 |
| 1400 | 900 | 790 | 610 | 180 | 720 |
| 1400 | 800 | 790 | 610 | 180 | 620 |
| 1300 | 900 | 740 | 560 | 180 | 720 |
| 1300 | 800 | 740 | 560 | 180 | 620 |
| 1200 | 1000 | 690 | 510 | 180 | 820 |
| 1200 | 900 | 690 | 510 | 180 | 720 |
| 1200 | 800 | 690 | 510 | 180 | 620 |
| 1200 | 760 | 690 | 510 | 180 | 580 |
| 1100 | 900 | 640 | 460 | 180 | 720 |
| 1100 | 800 | 640 | 460 | 180 | 620 |
| 1100 | 760 | 640 | 460 | 180 | 580 |
| 1000 | 900 | 590 | 410 | 180 | 720 |
| 1000 | 800 | 590 | 410 | 180 | 620 |
| 1000 | 760 | 590 | 410 | 180 | 580 |
| 900 | 800 | 540 | 360 | 180 | 620 |
| 900 | 760 | 540 | 360 | 180 | 580 |

3 Anti-Slip_ShowerTray_Rectangular Tray Size Schedule

NOTES:

WASTE
 SENSTEC shower trays have been designed exclusively for use with McAlpine ST90CPB-S-HP2 or ST90CPB-S-70, with flow rates of 42 and 34 litres per minute respectively when tested in accordance with EN274-2:2002. <http://mcalpineplumbing.com>

WATERPROOFING
 When installing a SENSTEC Anti-Slip shower tray it is recommended to use the Classi Bathroom Waterproofing range of products <http://waterproofyourbathroom.com/shower-trays>

CLEANING
 Ensure that the tray is washed with soap and water and dried with a soft cloth after each use.

ORIGINAL BY SENSTEC DATE 10/04/2019

Contact
 SENSTEC | 185 Omagh Road | Ballygawley | Dungannon | Co. Tyrone | N.Ireland | BT70 2AL

Drawing Name: Anti-Slip_ShowerTray_Rectangular Technical Data Sheet
 Drawing Number: SENSTEC-STC-XX-XX-DS-A-20-001
 Drawing Status: Information Rev: P1

THIS DRAWING IS PROPERTY OF SENSTEC AND REMAINS PROPERTY OF SENSTEC. ANY DRAWING DISCREPANCY SHOULD BE NOTIFIED TO THE DRAWING ORIGINATOR IMMEDIATELY. THIS DRAWING SHOULD NOT BE COPIED WITHOUT NOTIFICATION TO THE OWNER. THIS DRAWING IS FOR PLANNING PURPOSES ONLY & NO DIMENSIONS SCALING SHOULD BE USED FOR FABRICATION. ALL DIMENSIONS TO BE MEASURED ON SITE PRIOR TO MANUFACTURE OF ANY PROPOSALS